



Salt Union Ltd.

Astbury House Bradford Road Winsford CW7 2PA www.saltunion.com

T: +44 ()1606 596530

Safety Data Sheet

1

Identification of the Substance and Company

PRODUCT NAME: ROCK SALT:

DRYROX, 'THAWROX', 'BETROX'

Address/Phone Number: Salt Union Limited

Winsford Rock Salt Mine

Bradford Road

Winsford

Cheshire CW7 2PE Tel: 01606 592201

Emergency Phone Number: IN AN EMERGENCY DIAL 999

For specialist advice in an emergency telephone

Winsford (01606) 592201

2

Product Description

Rock Salt is approximately 94% pure salt and has a characteristic reddish-brown colour owing to the presence of marl (an insoluble mineral) which is the chief impurity. The salt is treated with approximately 30 ppm sodium ferrocyanide as an anticaking agent.

Alternative Names: Sodium Chloride, Common Salt, Halite

CAS Number: Sodium Chloride 007647-14-5

Sodium Ferrocyanide 13601-19-9

EINECS Number: Sodium Chloride 231-598-3

Sodium Ferrocyanide 237-081-9

HAZARDOUS INGREDIENT(S) Contains no Hazardous Ingredients

EC Directive 93/112/EEC

Hazards Identification

Unlikely to cause harmful effects under normal conditions of handling and use.

4

First Aid Measures

Inhalation: Remove patient from exposure.

Skin Contact: Wash skin with water.

Eye Contact: Irrigate with eyewash solution or clean water, holding

the eyelids apart, for at least 10 minutes. If symptoms develop, obtain medical attention.

Ingestion: Wash out mouth with water and give 200-300ml (half

a pint) of water to drink. Obtain medical attention if

ill-effects occur.

Further Medical Treatment: Symptomatic treatment and supportive therapy as

indicated.

5

Fire Fighting Measures

Non-combustible

Extinguishing Media: As appropriate for surrounding fire.

Fire Fighting Protective Equipment: No special requirements.

6

Accidental Release Measures

- Clear up spillages.
- Transfer to a container for disposal.
- Wash the spillage area with water.
- Spillages or uncontrolled discharges into water courses, drains or sewers must be IMMEDIATELY alerted to

the Environment Agency or other appropriate regulatory body

7

Handling and Storage

HANDLING Avoid contact with eyes. Avoid prolonged skin

contact. Atmospheric levels should be controlled in compliance with the occupational exposure limit for dust. Keep away from strong acids and common metals. Static electricity can be generated by pneumatic conveying, therefore pipes should be bonded and earthed, especially where a spark could

prove hazardous.

STORAGE

Keep away from concentrated acids. Rock salt can be stored outside but will absorb moisture over time. Care should be taken to avoid excessive run-off into

water or onto vegetation

8

Personal Protection and Exposure Controls

Wear suitable protective clothing, gloves and eye/face protection. An approved dust mask should be worn if exposure to levels above the occupational exposure limit is likely. Occupational Exposure Standard (UK HSE Guidance Note EH40)

Time Weighted Average

mg/m³ (ppm)

10

4

Dust (Total Inhalable Dust) Dust (Respirable Dust)

9

Physical and Chemical Properties

Form: Crystalline solid

Colour: Red-brown Odour: Odourless

Boiling Point (Deg C): 1413 Melting Point (Deg C): 802

Density of Sodium Chloride (g/ml): up to 2.165 at 20 Deg C

Bulk Density (g/ml): 1.2 to 1.5 approx

Solubility (Water): freely soluble, with some insoluble marlstone residue

NOMINAL PARTICLE SIZE RANGE:

Dryrox 10 0-10mm Dryrox 6 0-6mm Thawrox 10 0-10mm Thawrox 6 0-6mm

10

Stability and Reactivity

Hazardous Reactions: Reactions with concentrated acid will produce

> hydrogen chloride. Under wet conditions, will corrode many common metals, particularly iron, aluminium

and zinc.

11

Toxicological Information

Inhalation: High concentrations of dust may be an irritant to the

respiratory tract.

Skin Contact: Will remove the natural greases resulting in dryness,

cracking and possibly dermatitis. Repeated and /or

prolonged skin contact may cause irritation.

Eye Contact: Dust may cause irritation.

Ingestion: May cause vomiting and diarrhoea. The swallowing

of small amounts is unlikely to cause any adverse

effects.

Long Term Exposure: Repeated ingestion of excessive amounts may

cause disturbance of body electrolyte and fluid

balance.

12

Ecological Information

Environmental Fate and Distribution High tonnage material with wide disperse use. Solid

with low volatility. The product is soluble in water. The product has no potential for bioaccumulation. The product is predicted to have high mobility in soil.

Toxicity Low toxicity to aquatic organisms.

Effect on Effluent Treatment Adverse effects would not be expected.

13

Disposal Considerations

Disposal should be in accordance with local, national and European Community legislation

14

Transport Information

Not classified as dangerous for transport

15

Regulatory Information

Not classified as dangerous for supply or use

16

Other Information

USES: HIGHWAYS DE-ICING, FERTILISER, ANIMAL FEED ETC.

This data sheet was prepared in accordance with Directive 93/112/EC and the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994. Information in this publication is believed to be accurate and is given in good faith but the Customer should ensure the suitability for any particular purpose. Accordingly, Salt Union gives no warranty as to the fitness of the Product for use and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.

Any Trade marks herein identified are the property of Compass Minerals and Salt Union Limited.